



SPECIFICATION

Blood Pressure Monitor / FC-BP103



One-Button Operation



WHO Indicator



Optional: Voice Broadcast



Automatically Power Off



Intelligent Measurement



2*120 Memory Function

FC-BP103



FEATURES

- Arrhythmia detection
- LED Colorful Display
- Anti-shake function
- Self-check Cuff positioning
- High Brightness & Wide Viewing Angles

● SPECIFICATIONS

| | |
|-------------------------------|--|
| Model No. | FC-BP103 |
| Measurement Method | Oscillographic measurement method |
| Display | LED Digital Display |
| LED screen size | 80×95mm |
| Measurement Range | Blood Pressure range: 0~299mmHg (0 kPa - 39.9 kPa) Pulse: 40 to 180 beats/min |
| Accuracy of the cuff pressure | Static Pressure:±3mmHg(±0.4 kPa) Pulse rate: Within ±5% of reading |
| Inflation | Automatic inflation by pump |
| Deflation | Automatic rapid deflation |
| Pressure Detection | Semiconductor pressure sensor |
| Memory | 2 Users * 120 memories |
| Low voltage warning | When the voltage of the sphygmomanometer is lower than 4.4V±0.2V, the host and display screen should have a low voltage symbol display |
| Power supply | 4 AA alkaline batteries (not included), DC6V |
| | USB Type C(DC5V1A) |
| Battery life | Approximately 300 measurements when using alkaline batteries at the room temperature of 22° and by using three times a day and inflating to 170 mmHg |
| Storage Condition | Temperature: -4°F - 140°F(-20°Cto 55°C) Humidity: 0 - 95% RH Atmospheric pressure: 70kPa - 106kPa |
| Operating Condition | Temperature: 50°F to 104°F (10°C to 40°C) Humidity: 15 to 85% RH |
| Automatic Power-OFF | Within 2 Minutes |
| Weight | 472g (exclude batteries) |
| Product dimension | 109mm×137mm×73mm |
| Packing size | 110mm×95mm×160mm |
| Cuff | 9-17 inches(22-42cm) |
| Electric Shock Protection | Internal power supply appliance type B |
| Accessorial Components | Cuff, Instruction Manual |
| Service Life | 5 Years |