


SPECIFICATION

Blood Pressure Monitor / FC-BP210



- ① Set Button
- ② Start/Stop Button
- ③ Memory Button
- ④ LCD Display Screen
- ⑤ Wrist cuff



One-Button Operation



WHO Indicator



Optional:
Bluetooth/Voice Broadcast



Automatically Power Off



Intelligent Measurement



2*120 Memory Function

FC-BP210



FEATURES

- Average Value Function
- LCD Display Screen
- Cuff Self-checking
- Movement Error Checking
- Irregular Heartbeat Indicator

● SPECIFICATIONS

Model No.	FC-BP210
Measurement Method	Oscillographic measurement method
Display	LCD Display Screen
LCD screen size	41×43mm
Measurement Range	Blood Pressure range: 0~280mmHg (0 kPa - 37.3 kPa) Pulse: 40 to 180 beats/min
Accuracy of the cuff pressure	Static Pressure:±3mmHg(±0.4 kPa) Pulse rate: Within ±5% of reading
Pressure Detection	Semiconductor pressure sensor
Memory	2 Users * 120 memories
Low voltage warning	When the voltage of the sphygmomanometer is lower than 4.4V±0.2V, the host and display screen should have a low voltage symbol display
Power supply	2 AAA alkaline batteries (not included), DC3V
Battery life	Approximately 300 measurements when using alkaline batteries at the room temperature of 22°C and by using three times a day and inflating to 170 mmHg
Storage Condition	Temperature: -4°F - 140°F(-20°Cto 55°C) Humidity: 0 - 95% RH Atmospheric pressure: 70kPa - 106kPa
Operating Condition	Temperature: 50°F to 104°F (10°C to 40°C) Humidity: 15 to 85% RH
Automatic Power-OFF	Within 2 Minutes
Weight	95.4g (exclude batteries)
Product dimension	80.4*65.5*24mm
Packing size	/
Wrist cuff	5.31-7.67 inches(13.5-21.5cm)
Electric Shock Protection	Internal power supply appliance type B
Accessorial Components	Wrist cuff, Instruction Manual
Service Life	5 Years